

# Jetline Selection Fi



## The new-generation Jetline!

The Jetline Selection Fi combines power, quiet operation, and energy savings. Thanks to Full Inverter technology, it continuously adjusts its output to maintain a stable temperature with optimal efficiency. Available in 8 power levels from 7 to 30 kW, it adapts to pools up to 150 m<sup>3</sup>.

➤ **Full Inverter Technology** : Efficient and economical with a COP of up to 6.

➤ **Reversible heating/cooling** : Heat or cool your pool depending on the season, or let the heat pump automatically adjust to the ideal temperature.

➤ **Single-phase & Three-phase** : Available in both single-phase and three-phase versions to suit all electrical installations.

➤ **Remote control** : Manage your heat pump remotely via Wi-Fi and the Poolex app.

|                    | 75               | 95               | 125              | 155              | 210               | 155 Tri          | 210 Tri           | 310 Tri           |
|--------------------|------------------|------------------|------------------|------------------|-------------------|------------------|-------------------|-------------------|
| <b>Pool volume</b> | 45m <sup>3</sup> | 50m <sup>3</sup> | 65m <sup>3</sup> | 80m <sup>3</sup> | 110m <sup>3</sup> | 80m <sup>3</sup> | 110m <sup>3</sup> | 150m <sup>3</sup> |



Application  
**POOLEX**

App Store

Google Play



Compatible with  
all treatments

### WARRANTIES

On-site heat pump\* **2 years**

Compressor **5 years**

Titanium coil (corrosion-resistant) **15 years**

## Still just as efficient, the new Poolex Jetline Selection Fi, with its unbeatable quality/performance/price ratio, is the benchmark for swimming pool heat pumps.

Its Full Inverter technology allows it to vary not only the compressor speed but also the fan speed, enabling it to perfectly adapt to demand and therefore reduce both electricity consumption and noise levels.

Thanks to its design and large hydrophilic aluminum evaporation surface, the Poolex Jetline Selection Fi operates down to temperatures as low as -7°C.

With the new Twisted Tech® heat exchanger featuring a twisted titanium coil, the pool heats up even faster.

Available in 5 power levels, from 7.1 to 20.1 kW, it is suitable for pools up to 150 m<sup>3</sup>.

| Jetline Selection Fi                   |                        | 75                       | 95         | 125        | 155         | 210        | 155 TRI           | 210 TRI     | 310 TRI      |
|--|------------------------|--------------------------|------------|------------|-------------|------------|-------------------|-------------|--------------|
| Pool volume (m³)                       |                        | 45                       | 50         | 65         | 80          | 110        | 80                | 110         | 150          |
| Reference:                             |                        | PC-JLS075N               | PC-JLS095N | PC-JLS125N | PC-JLS155N  | PC-JLS210N | PC-JLS155TN       | PC-JLS210TN | PC-JLS310TN  |
| Air 26°C<br>Water 26°C<br>Humidity 80% | Power consumption (kW) | 1.15                     | 1.51       | 2.07       | 2.37        | 3.14       | 2.37              | 3.14        | 5.65         |
|  | COP                    | 6.00                     | 5.70       | 5.70       | 6.00        | 5.60       | 6.00              | 5.60        | 5.40         |
|  | Heating capacity (kW)  | 6.90                     | 8.60       | 11.80      | 14.20       | 17.60      | 14.20             | 17.60       | 30.50        |
| Air 15°C<br>Water 26°C<br>Humidity 70% | Power consumption (kW) | 1.10                     | 1.30       | 1.89       | 2.22        | 2.98       | 2.22              | 2.98        | 5.22         |
|  | COP                    | 4.80                     | 4.70       | 4.60       | 4.50        | 4.50       | 4.50              | 4.50        | 4.60         |
|  | Heating capacity (kW)  | 5.30                     | 6.10       | 8.70       | 10.00       | 13.40      | 10.00             | 13.40       | 24.00        |
| Power supply                           |                        | 220-240V~50Hz            |            |            |             |            | 380-415V~ 3N 50Hz |             |              |
| Heating temperature range              |                        | 15~40°C                  |            |            |             |            |                   |             |              |
| Operating range                        |                        | -7~43°C                  |            |            |             |            |                   |             |              |
| Max. power input (kW)                  |                        | 1.8                      | 2          | 3          | 3.5         | 4          | 5.5               | 6.5         | 10           |
| Flow rate (m³/h)                       |                        | 3                        | 3.5        | 5          | 6           | 6          | 8                 | 8           | 8            |
| Circuit breaker (A)                    |                        | 10                       | 16         |            | 20          | 25         | 10                | 16          | 20           |
| Cable diameter (at 10 m)               |                        | 3x2.5 mm²                |            |            | 3x4mm²      |            | 3x2.5 mm²         |             |              |
| Refrigerant                            |                        | R32                      |            |            |             |            |                   |             |              |
| Dimensions (mm)                        |                        | 865x375x656              |            |            | 945x375x656 |            | 1143x395x756      |             | 1172x545x856 |
| Net / gross weight (kg)                |                        | 35.5                     | 38         | 41         | 47.5        | 50         | 58                | 60.5        | 95           |
| Noise level at 1 m (dB(A))             |                        | 37~50                    | 37~51      | 38~52      | 40~55       | 40~55      | 41~55             | 41~55       | 50~65        |
| Noise level at 10 m (dB(A))            |                        | 19~29                    | 19~30      | 21~31      | 23~35       | 23~35      | 23~35             | 23~35       | 29~39        |
| Compressor brand                       |                        | MITSUBISHI               |            |            |             |            |                   |             | GMCC         |
| Heat exchanger                         |                        | Twisted Tech© Titane     |            |            |             |            |                   |             |              |
| Function                               |                        | Heating / Cooling / Auto |            |            |             |            |                   |             |              |
| Pressure drop (mCE)                    |                        | 1,1                      | 1,1        | 1,1        | 1,1         | 1,1        | 1,1               | 1,1         | 1,1          |

### Included accessories




Delivery on a wooden pallet



Insulated winter cover



Anti-vibration support kit



PVC connectors Ø 50 mm - 1 1/2



Wired control extension (10 m)



Condensate drainage hose



Maintenance kit including the multilingual user manual