

MEGALINE Fi

Full Inverter technology serving communities

• Optimized performances for very large volumes


Stainless steels structure

G Full Inverter technology

⇔ Twin rotary compressor

➡ WiFi control

	50	70	100
Swimming pool volume	Contact our experts for a detailed analysis		
COP air 15°C /water 26°c	4.93~ 7.52	5.05~ 7.65	4.99~7.58
Noise level at 10 m (db(a))	<40	<50	<42



HEAT PUMP WARRANTY ON SITE*

3 YEARS

COMPRESSOR WARRANTY

TITANIUM COIL



Limitless Efficiency

The Megaline Fi is adaptable to all swimming pools, even with the biggest volumes. Connect several MEGALINE FI to multiply their heating capacity.

















FOR PRIVATE AND PUBLIC POOLS

OPERATES 3 versions available



	MEGALINE FI	50	70	100		
Swimming	pool volume		Ask for a personal analysis			
Reference: P	C-mlp	502N	703N	1002N		
Air 26°C Water 26°C Hygro 80%	Max. Power output (kW)	68	89,80	135		
	Min. Power output (kW)	16.1	22,62	31.9		
	Power consumption (kW)	9.8~1.2	1,42~13,58	19.3~2.3		
	COP	13.54~6.93	6,61~15,93	13.59~6.98		
Air 15°C Water 26°C Hygro 70%	Max. Power output (kW)	50	70	100	ا ۾	
	Min. Power output (kW)	11.7	21,43	23.6	NDAI	
	Power consumption (kW)	10.1~1.6	3,05~13,65	20.0~3.1	E.U STANDARD	
	COP	7.52~4.93	5,05~7.65	7.58~4.99		
Electric supp	ly	Tri 380V/3/50Hz				
Heating temperature range			15°C~40°C		Data provided for information purposes only. Can be subject to change without notice	
Cooling temperature range			8°C~28°C		e with	
Operating ra	nge		-15°C~43°C		hang	
Max. capacit	y (kW)	14.9	20	29.8	t to c	
Flow (m ³ /h)		20	35	40	ubjec	
Refrigerant			R32/5,7KG*2		be sı	
Dimensions	(mm)	1448x800x950	1252×1075×2428	2148×1076×2176	. Can	
Hydraulic cor	nnections (mm)	63	75	75	only	
Max. intensit	y (A)	27	35	53	boses	
Electric sizing	g at 10m	R02V 5 x 6mm ²	RO2V 5 x 10mm ²	R02V 5 x 16mm ²	n bur	
Net weight (F	(g)	280	448	760	natio	
Noise level a	t 1 m (dB(A))	≤70	≤70	≤73	inforr	
Noise level a	t 10 m (dB(A))	≤40	≤50	≤42	d for	
Compressor	type		Rotary Inverter		ovide	
Compressor brand		Mitsubishi				
Number of compressors		1	2	2	Da	
Heat exchan	ger	Twisted Tech© Titanium				
Function		Heating (Full Inverter) / Cooling (Full Inverter) / Silence / Auto				
Load losses	(mCE)	4		4.8		





Large color display control panel



WiFi Connection for remote monitoring



Anticorrosion stainless steel structure



Large operating range up to -15°C



Large connections for professional swimming pools

The Megaline Fi is part of the new generation heat pumps dedicated to communities.

With its Full Inverter Technology, the Megaline Fi modifies its output accordingly. Both compressors and fans adjust their frequencies in real time to only supply the necessary power. Consequently, electrical consumption drops as well as sound pressure to let the heat pump go unnoticed.

The touch screen control panel allows for a more intuitive use of the Megaline Fi. You can also download the Smart Life application to control the heat pump wherever you are.

Equipped with a stainless steel structure and a powder-coated galvanized steel casing, the Megaline Fi is ready to meet

any challenge. Furthermore, its new generation Mitsubishi compressors use R32 gas, a more environmental friendly and more efficient refrigerant than the R410.

Its connections for large volumes enable it to naturally adapt itself to the flow constraints found with public equipment.

Confident of the reliability of its product range, Poolstar extends its warranty to 3 years on the heat pump, 5 years on the compressor and 15 years on the heat exchanger against any corrosion.



For more information on our products and services **poolstar.fr/en**

