POOLEX
FOLLOW THE EXPERT



SPAWER

O'SPA Flow

3kW **5kW** **7kW**

The SPA heat pump with integrated circulation

Thanks to its integrated circulation pump, the O'SPA Flow connects directly to the SPA, without a bypass. It manages both heating and cooling temperatures, down to ice bath mode, for easy use and precise control all year round.

- **Integrated circulation pump :** Constant flow rate adapted to SPAs, without bypass, ensuring stable flow through the heat exchanger for simplified installation and optimized thermal regulation.
- **SPA heater control via integrated relay :** The O'SPA Flow can control the spa's electric heater via an integrated relay, ensuring heating continuity when required.
- **Complete thermal management :** High-efficiency heating and integrated chiller.
- **Compact & premium design :** With its compact format, clean aesthetics and decorative grilles, the O'SPA Flow is designed to blend naturally next to the SPA.
- **The heat pump covers all SPA thermal needs :** Fast temperature rise, precise temperature maintenance, cooling during hot periods or for cold baths, and automatic mode for hands-free operation.



App POOLEX

App Store

Google Play

R32 OZONE FRIENDLY

Compatible with all water treatments

Built-in WiFi

WARRANTIES

Heat pump	2 YEARS
Compressor	5 YEARS
Titanium coil (anti-corrosion	10 YEARS

www.poolex.fr

O'SPA FLOW		3 kW	5 KW	7 KW
Reference : PC-OSPA		35P	55P	75P
Recommended climate (heating)		Warm	Temperate	
Air 26°C Water 26°C Humidity 80%	**Capacity (kW)**	**3,30**	**5,06**	**7,10**
	Power consumption (kW)	**0,66**	**0,95**	**1,28**
	COP	**5**	**5,30**	**5,55**
Air 15°C Water 38°C Humidity 70%	Capacity (kW)	2,11	3,25	4,65
	Power consumption (kW)	0,75	1,08	1,37
	COP	2,75	3,00	3,40
Recommended climate (cooling)		Temperate		Warm
Air 35°C Water 27°C Humidity 70%	Capacity (kW)	2,00	2,75	3,90
	Power consumption (kW)	0,98	1,38	1,66
	EER	2,05	2,00	2,35
Air 15°C Water 5°C Humidity 70%	**Capacity (kW)**	**1,45**	**2,00**	**2,90**
	Power consumption (kW)	**0,62**	**0,76**	**1,00**
	EER	**2,35**	**2,55**	**2,90**
Power supply		Single-phase 220–240V ~ 50Hz		
Connections		32 / 38mm		
Max power (kW)		1,30	1,80	2,55
Heating temperature range		10°C / 40°C		
Cooling range		2°C / 30°C		
Operating range (heating/cooling)		-10°C~43°C / 7°C~40°C		
Flow rate (m³/h)		1,40	2,15	3,00
Refrigerant		R32 / 0,24 kg	R32 / 0,40 kg	R32 / 0,45 kg
Dimensions (mm)		520x490x390		620x490x420
Net / gross weight (kg)		33 / 38	38 / 43	47 / 50
Noise at 1 m (dB(A))		< 50	< 50	< 55
Noise at 10 m (dB(A))		< 30	< 30	< 35
Compressor type		Rotary		
Heat exchanger		Twisted Tech© Titane		
Function		Heating + Chiller + Auto + SPA heater relay control		
Pressure drop (mCW)		2,5	2,5	3,0

Specially developed for spas, Nordic baths and small pools, the O'SPA Flow combines heating, cooling and water circulation in a compact unit.

Its integrated circulation pump eliminates the need for a bypass and ensures a stable flow rate, perfectly suited to spas (simple connection).

Thanks to its chiller function, it can lower the water temperature down to 2°C, ideal for cold baths, recovery or hot climates. Available in 3 kW, 5 kW and 7 kW, it adapts to all configurations and ensures optimal operation thanks to its ON/OFF mode calibrated according to ambient temperature.

The O'SPA Flow offers simple and intuitive connected control, allowing remote adjustment of temperature and operating modes via the Poolex mobile app.

COMPACT DIMENSIONS :





Accessories

INCLUDED


Control relay


Residual current device with 5 m cable


Hydraulic connectors (2 sets)


Hose clamps (2 sets)


NetSpa kit connectors

OPTIONAL


Remote touchscreen


Hydraulic connection kit

POOLEX is a brand of the group **POOLSTAR**

Edition 12/2025 - Photos are non-contractual