Poolstar
Pure innovation

FOR POOLS
up to 110m³

EFFICIENCY
Amazing prize!

7 versions
available

POOLEX
FOLLOW THE EXPERT
SILVERLINE



SILVERLINE

Efficiency at an amazing prize!

- High perfomance compressor
- Ultra silent & economical
- Anti-corrosion / Anti-UV Metal casing
- Twisted Tech Titanium heat exchanger

HEAT PUMP WARRANTY SERVICES AND PARTS 2 ANS

COMPRESSEUR GARANTI 5 ANS

SERPENTIN EN TITANE GARANTI CONTRE LA CORROSION 15 ANS

	55	70	90	120	150	180	220
Swimming pool volume	20-30m³	30-40m³	40-50m³	45-65m³	65-75m³	70-90m³	80-110m³
COP air 26°C /water 26°c	6.13	6.21	6.17	6.22	6.20	6.20	6.19
Noise level at 10 m (db(a))	<30	<36	<37	<38	<39	<40	<40

PATENTED ANTIFREEZE SYSTEM

SILENT EFFICIENCY

NEW R32 OZONE FRIENDLY

COMPRESSOR TOSHIBA INSIDE

WiFi

TRAITEMENT SEL

Poolstar
Pure innovation

FOR POOLS
up to 110m³

EFFICIENCY
Amazing prize!

7 versions
available

POOLEX
FOLLOW THE EXPERT
SILVERLINE

POOLEX SILVERLINE		55	70	90	120	150	180	220
Swimming pool volume		**20-30m3**	**30-40m3**	**40-50m3**	**45-65m3**	**65-75m3**	**70-90m3**	**80-110m3**
Reference		PC-SLP055	PC-SLP070	PC-SLP090	PC-SLP120	PC-SLP150	PC-SILVERPRO-180	PC-SILVERPRO-220
Air 26°C Water 26°C Hygro 80%	**Capacity (kW)**	**5.39**	**7.02**	**9.31**	**12.5**	**15.24**	**17.92**	**21.72**
	Power consumption (kW)	**0.88**	**1.13**	**1.51**	**2.01**	**2.46**	**2.89**	**3.51**
	COP	**6.13**	**6.21**	**6.17**	**6.22**	**6.2**	**6.2**	**6.19**
Air 15°C Water 26°C Hygro 70%	Capacity (kW)	3.9	5.07	7.05	9.05	10.59	12.6	15.3
	Power consumption (kW)	0.81	1.01	1.39	1.78	2.07	2.47	2.98
	COP	4.84	5.02	5.07	5.08	5.12	5.1	5.13
Electricity supply		Mono 230V / 50Hz						
Max Power (kW)		1.29	1.83	2.51	3.03	3.58	4.43	5.46
Max Current (A)		6.26	8.85	11.52	14.5	16.41	19.65	24.22
Heating temperature range		15°C / 40°C						
Operating range		5°C / 43°C						
Flow (m³/h)		1.86	2.5	3.2	4.01	4.7	5.6	7
Refrigerant		R32					R410A	
Packaging dimensions (mm)		845x330x610	905x350x645	1005x350x750				1150x425x820
Dimensions (mm)		765x310x490	827x340x531	927x340x636				1067x405x692
Net / Gross weight (kg)		39 / 44	41 / 50	49 / 59	42 / 62	54 / 64	62 / 72	62 / 72
Noise level at 1 m (dB(A))		<46	<46	<47	<48	<49	<51	<51
Noise level at 4 m (dB(A))		<39	<40	<42	<43	<45	<46	<46
Noise level at 10 m (dB(A))		**<30**	**<36**	**<37**	**<38**	**<39**	**<40**	**<40**
Compressor type		Rotary						
Compressor brand		**Toshiba**						
Heat exhanger		Twisted Tech© Titanium						
Function		**Heating**						
Load losses (mCE)		0.9	0.9	1	1.10	1.13	1.15	nc

E.U. STANDARD
T.U.V. CERTIFIED

Data provided for information purposes only. Can be subject to change without notice.

Poolex Silverline: The best compromise between efficiency and prize.

A high-performance Mitsubishi compressor and a new titanium double-spiral heat-exchanger give it a COP above 6, based on 26/26 conditions*.

Simple to use, the Poolex Silverline has an LCD control panel that can be remotely positioned at up to 10m and includes Touch & Go technology.

Available in 7 output ratings from 5.5 to 22 kW, it is suitable for pools up to 110 m3.

Poolex performance at the lowest price.

The POOLEX + : all accessories included


Delivered on wooden pallet


Anti-vibration support kit


Ø 50mm 1" ½ Connectors PVC


Wired control extension (10m)


Condensation drainage pipe



Maintenance kit Including multi-language usermanual

Poolstar
Pure innovation

For more information on our our produics and services
www.poolstar.fr

AUTHORIZED RESELLER

Novmebre 2020 Edition

WWW.POOLSTAR.FR